S3019E ELECTRIC DRIVE SLAB SCISSOR LIFT



- Revolutionary design that redefines the electric scissor lift
- All-electric drive and steering no hydraulic hoses
- Features a sunken scissor stack for low platform step-in height
- Drives through a standard door way without folding handrails
- Zero inside turning radius for maximum manoeuvrability





ELECTRIC DRIVE SLAB SCISSOR LIFT


DIMENSIONS	20105
	S3019E 7.79m
Max. working height	
Max. platform height (A)	5.79m
Platform size (stowed)	0.61m x 1.69m
Platform size (extended)	0.61m x 2.6m
Deck extension length	0.91m
Overall length (C) (with step)	1.91m
Overall width (D)	0.77m
Stowed height (B)	1.76m
Ground clearance (stowed)	76mm
Ground clearance (elevated)	15mm
PERFORMANCE	
Platform capacity (SWL)	250kg
Max. drive height	5.79m
Max. wind speed	12.5m/s
Max. drive speed (stowed)	2.4km/h
Max. drive speed (elevated)	0.8km/h
Raise/lower time	30/44sec
Gradeability	25%
Inside turning radius	0m
Outside turning radius	1.77m
Tires	323mm x 102mm non-marking solid rubber
Controls	proportional
Drive system	2-wheel electric drive
POWER	
Power source	24V DC battery electric
Charger	90-240V, 25amp
WEIGHT	

Weight

TURNING RADIUS







STANDARD FEATURES

- All electric drive
- Electric steering
- Zero inside turning radius
- No hydraulic hoses
- Roll-out deck extension with dual locks
- Non-marking tires
- Swing-out service trays
- Saloon-door style entry gates
- Descent alarm
- All motion alarm
- 2 persons indoor
- 1 person outdoor
- Proportional controls, including descent
- Power line to platform
- Flashing amber light
- Hour meter & on-board diagnostics display
- Integrated battery charger
- Battery condition indicator
- Crane & forklift points
- Dual lanyard attachments points
- 2 year parts & labor, 5 year structural warranty
 - ANSI compliant

OPTIONS

•

1,588kg

- Special paint colors
- Airline to platform
- Environmental hydraulic oil
- Snorkel OnSite[™] telematics



P.O. Box 1160 St.Joseph, MO 64502-1160, USA Tel: 1 (785) 989-3000 Toll-free: 1 (800) 255-0317 Fax: 1 (785) 989-3070 Email: sales.usa@snorkellifts.com

S3019E